

KVSU28, Mechanical Connector with Spacer Bar

By Burndy
Catalog # [KVSU28](#)



Tin plated copper alloy with tin plated hardware; spacer bar to separate dissimilar conductors

Features

- Compact, tin-plated high strength copper alloy connector with spacer and tin-plated silicon bronze hardware
- Recommended for heavy duty connections
- Spacer separates dissimilar conductors and provides long contact length
- Neoprene ring prevents loss of shorter bolt during installation
- Longer peened bolt permits swivel action for easier installation

Application

For All Combinations Of Copper, Aluminum, ACSR, AAAC And 5005

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - Galvanized Steel Str Run Range	3/8 in- 1/2 in
Conductor - Galvanized Steel Str Tap Range	5/32 in- 1/2 in
Conductor - ACSR Str Run Range	1/0 ACSR - 4/0 ACSR
Conductor - ACSR Str Tap Range	6 ACSR - 4/0 ACSR
Conductor - AL Str Run Range	1/0 str. - 4/0 str.
Conductor - AL Str Tap Range	6 str.- 4/0 str.
Conductor - Copper Solid Run Range	<ul style="list-style-type: none"> • 2/0 AWG • 3/0 AWG • 4/0 AWG
Conductor - Copper Solid Run Range	2/0 AWG-4/0 AWG
Conductor - Copper Solid Tap Range	<ul style="list-style-type: none"> • 2/0 AWG • 3/0 AWG • 4/0 AWG

Conductor - Copper Solid Tap Range 2/0 AWG-4/0 AWG

Conductor - Copper Str Run Range 1/0 str. - 4/0 str.

Conductor - Copper Str Tap Range 6 str.- 4/0 str.

Conductor Type

- AL C Str-Run
- AL C Str-Tap
- CU C Str-Run
- CU C Str-Tap
- AAAC C 5005-Run
- AAAC C 5005-Tap
- AAAC C 6201-Run
- AAAC C 6201-Tap
- ACSR C Str-Run
- ACSR C Str-Tap
- CU C Solid-Run
- CU C Solid-Tap
- GAL Steel C Str-Run
- GAL Steel C Str-Tap
- Cu Weld Sol.- Run
- Cu Weld Sol.- Tap

Conductor - CopperWeld Solid Run Range 2/0 sol.- 4/0 sol.

Conductor - CopperWeld Solid Tap Range 6 sol.- 4/0 sol.

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Dimension - L Length Overall mm	29 mm
Dimension - Height fraction	2-3/8 in
Dimension - Height inch	2.50 in
Package Height	0.000 in
Dimension - Height mm	63.50 mm
Dimension - Stud Size inch	3/8 in
Dimension - Width fraction	1-3/4 in
Dimension - Width inch	1.67 in
Dimension - Width mm	44 mm
Dimension - Length Overall inch	1.04 in

Force Related

Installation Torque 250 LBS/in
Recommended in-lb

Plating Type Tin
Finish Type Tin-Plated
UPC 781810081808

General

Trade Name OKLIP™
Sub Brand OKLIP
Plated Y
Construction Material - Main Copper alloy
Type KVS, Compact, Universal
UPC 12 Digit 781810081808
UPC 14 Digit GTIN 00781810081808
Material Copper

Logistics

Minimum Pack Quantity 1
Carton Quantity 25
Pallet Quantity 3000

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2026 Hubbell Incorporated. All rights reserved
BRDY-KVSU28-SPEC-EN | REV 4/2026