

PENETROX Bottle 8 Ounce

By Burndy
Catalog # P8A

PENETROX Bottle 8 Ounce



Features

- PENETROX™ Oxide Inhibiting Joint Compounds are available in many types
- PENETROX A is a natural compound recommended for aluminum to aluminum, aluminum to copper connections and aluminum conduit threads, it is not recommended for use with rubber or polyethylene insulated conductors
- PENETROX A13 is a synthetic base compound with evenly suspended zinc particles recommended for aluminum to aluminum, aluminum to copper, and also aluminum conduit threads
- PENETROX E is a synthetic base with evenly suspended copper particles, recommended for copper to copper, copper threads, and all grounding applications

Application

Aluminum to Aluminum, Aluminum to Conduit, Aluminum to Copper

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	TAA Compliant (All status valid till December 2026)
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes

Dimensions

Package Length	0.000 in
Package Width	0.000 in
Package Weight	0.000 lb.
Package Height	0.000 in

General

Trade Name	PENETROX™
Pour Point	-15 °F
Container Type	Squeeze Bottle
Sub Brand	PENETROX
Application - For Use On	<ul style="list-style-type: none"> • Aluminum to Aluminum • Aluminum to Conduit • Aluminum to Copper
Type	Sealing compound
UPC 12 Digit	781810592557
UPC 14 Digit GTIN	00781810592557
UPC	781810592557

Logistics

Minimum Pack Quantity	1
Carton Quantity	12
Pallet Quantity	1680
Container Size	8 oz

Operational

Temperature - Dropping Point Fahrenheit	230 °F
Viscosity at 100 Fahrenheit	305 °F

Product Assets

[Catalog \[English\]](#)