

### PR-59



Especificaciones		
Modelo		PR-59
Resistance ( $\Omega$ )	20 $\Omega$ /200 $\Omega$ /2K $\Omega$ /20K $\Omega$ /200K $\Omega$ /2M $\Omega$ /20M $\Omega$ /200M $\Omega$ /2000M $\Omega$ 20 $\Omega$ /200 $\Omega$ /2K $\Omega$ /20K $\Omega$ /200K $\Omega$ /2M $\Omega$ /20M $\Omega$ /2000M $\Omega$ 200 $\Omega$ /2K $\Omega$ /20K $\Omega$ /200K $\Omega$ /2M $\Omega$ /20M $\Omega$	$\pm(0.8\%+1)$
Capacitance (F)	200pF/2nF/20nF/200nF/2uF/20uF/200u F/2mF/20mF 2nF/20nF/200nF/2uF/20uF/200uF/600u F	$\pm(0.5\%+10)$
Inductance (H)	2mH/20mH/200mH/2H/20H/200H 2mH/20mH/200mH/2H/20H	
Features		
Display Count		1999
Manual Range		✓
Diode		28mm
Transistor		✓
Continuity Buzzer	0.1%~99.9%	✓
Low Battery Indication		✓
Data Hold		
General Characteristic		
Power	9V Battery (6F22)	
LCD Size	61mm X 32 mm	
Product Color	Red and Grey	
Product Net Weight	R-59-310g	
Product Size	172mm X 83mm X38 mm	
Standard Accessories	Battery, Test Clip,Holster	
Standard Individual Packing	Gift Box, English Manual	
Standard Quantity Per Carton	40 PCs	
Standard Carton Measurement	598mm X 418mm X 340mm (0.085 CBM Per Standard Carton)	
Standard Carton Gross Weight	21Kg	