

FICHA TECNICA

10465-TB

Archivo 110 de 170

IDENTIFICACION VERIFICADA

CODIGO SOLICITADO	10465-TB
FABRICANTE TECNICO	ABB Installation Products / T&B Fittings
FAMILIA	Teck cable sealing / end fitting accessory
REFERENCIA LOCALIZADA	10465-TB

FUENTE DOCUMENTAL

DOCUMENTO OFICIAL	ABB - Star Teck / Teck and Tray Cable Fittings Catalog
PAGINA(S) ANEXADA(S)	29
ENLACE DE ORIGEN	https://tnb.ca.abb.com/en/pdf-catalogues/fittings-and-conduit-systems/teck-and-tray-cable-fittings/A-Teck-and-Tray-Cable-Fittings-E.pdf

ALCANCE DEL ARCHIVO

La(s) pagina(s) siguiente(s) provienen de la documentacion tecnica indicada y contienen la tabla, dimensiones, materiales, certificaciones o notas de aplicacion asociadas al codigo. Esta portada individual permite identificar el producto y mantener el nombre exacto requerido para la carga masiva.

10464 Series watertight fittings for ACWU cable



	Cat. no.	Hub size (in.)	Cable jacket O.D. (in.)		Throat dia. (in.)
			Min.	Max.	
	10462*	½	0.562	0.625	0.615
	10464	½	0.625	0.760	0.615
	10465-TB	½	0.750	0.885	0.615
	10466	½	0.875	0.985	0.615
	10467	¾	0.880	1.065	0.780
	10468	¾	1.055	1.205	0.780
	10469	1	1.187	1.375	1.000
	10470	1¼	1.375	1.625	1.187
	10550	1¼	1.375	1.625	1.400
	10471	1¼	1.625	1.875	1.400
	10472	1½	1.750	1.965	1.563
	10473	1½	1.937	2.187	1.621
	10551	2	2.000	2.187	2.000
	10474	2	2.156	2.360	2.000
	10475	2	2.350	2.565	2.000
	10552	2	2.350	2.565	2.092
	10476	2	2.535	2.750	2.092
	10553	2½	2.535	2.750	2.437
	10477	2½	2.735	2.985	2.437
	10478	2½	2.970	3.220	2.437
	10554	3	2.975	3.125	3.050
	10555	3	3.080	3.250	3.050
	10479	3	3.210	3.380	3.050
	10480	3	3.310	3.480	3.050
	10481	3½	3.430	3.620	3.310
	10482	3½	3.560	3.750	3.310
	10483	3½	3.710	3.870	3.310
	10484	4	3.810	4.000	3.560
	10485	4	3.930	4.120	3.670
	10486	4	4.060	4.250	3.800

Note - When using fittings on single-conductor cable, aluminum fittings and aluminum locknuts must be used.

*Cat. no. 10462 not UL Listed

Materials

- Malleable iron: The above listed catalogue numbers relate to malleable iron fittings with a protective grounding sleeve for jacketed metal-clad cable.
- Aluminum: Available up to 21/2 inches. To order add suffix "AL" to the catalogue number (example 10478AL).
- PVC-coated aluminum and steel: Contact your regional sales office for availability and ordering information.

Certifications

- Type HLA. CSA certified Classes I, II and III. These fittings are suitable for Class I hazardous locations when used in combination with a certified Class I hazardous location sealing fitting.
- Type OLA. UL listed. These fittings are suitable for use interlocked jacketed cable, aluminum or steel armour.