

FICHA TECNICA

H100-TB

Archivo 065 de 170

IDENTIFICACION VERIFICADA

CODIGO SOLICITADO	H100-TB
FABRICANTE TECNICO	ABB Installation Products / T&B Fittings
FAMILIA	T&B hub connector
REFERENCIA LOCALIZADA	H100-TB

FUENTE DOCUMENTAL

DOCUMENTO OFICIAL	ABB - T&B Rigid Fittings Catalog
PAGINA(S) ANEXADA(S)	17
ENLACE DE ORIGEN	https://library.e.abb.com/public/b94e4970ad794fc1939233429e081151/TBRigidFittings_catalog.pdf

ALCANCE DEL ARCHIVO

La(s) pagina(s) siguiente(s) provienen de la documentacion tecnica indicada y contienen la tabla, dimensiones, materiales, certificaciones o notas de aplicacion asociadas al codigo. Esta portada individual permite identificar el producto y mantener el nombre exacto requerido para la carga masiva.

Hubs and Bulkhead Fittings

T&B® Hub



Never before has a single hub fit like this one. Designed for unequalled performance. The innovative engineering of the T&B® Hub will, quite simply, raise your performance expectations for threaded hubs. Look for the distinctive blue color to ensure the quality of a Thomas & Betts fitting.

- 1 Sealing Ring and Groove with innovative profile outperforms standard O-ring design. Sealing ring is captivated in place before installation and resists buckling or slipping during installation. The seal groove is designed for optimum compression of the sealing ring. The sealing ring is designed to provide a complete 360° seal, even when the conduit is not perpendicular with the enclosure. (See Figure 1)
- 2 Locknut Design with peripheral slots and a hexagonal/angled spline spaced every 30° enables easy application of torque with wrench or hammer and screwdriver. (See Figures 2 & 3)
- 3 Sharper and Deeper Teeth on locknut and body designed for a more penetrating bite for improved bonding to the enclosure.
- 4 Hexagonal/Splined Body Design for fast, easy installation with wrench or hammer and screwdriver.
- 5 Precision Machined Tapered Threads designed to create watertight union.
- 6 Insulated Throat molded from 105° C rated thermoplastic with a flammability rating of 94 V-0.




Fig. 1




Fig. 2




Fig. 3



CAT. NO.	A		B		C		D		E	
	TRADE SIZE	DIA.	TRADE SIZE	DIA.	TRADE SIZE	DIA.	MAX. PANEL THICKNESS	THROAT DIA.	TRADE SIZE	DIA.
H050-TB	1/2	1 1/16	1 1/16	1 1/16	7/8	7/8	3/16	1 1/32	1 1/2	1 1/2
H075-TB	3/4	1 1/8	1 1/8	1 1/8	1 1/4	1 1/4	3/16	1 1/8	1 3/4	1 3/4
H100-TB	1	1 3/8	1 3/8	1 3/8	1 1/2	1 1/2	1/4	1 1/4	2	2
H125-TB	1 1/4	2 1/8	2 1/8	2 1/8	1 3/4	1 3/4	1/4	1 1/2	2 1/4	2 1/4
H150-TB	1 1/2	2 3/8	2 3/8	2 3/8	2	2	1/4	1 3/4	2 1/2	2 1/2
H200-TB	2	3 1/4	3 1/4	3 1/4	2 1/2	2 1/2	1/4	2 1/4	3	3
H250-TB	2 1/2	3 3/4	3 3/4	3 3/4	3	3	1/4	2 3/4	3 1/2	3 1/2
H300-TB	3	4 1/8	4 1/8	4 1/8	3 1/2	3 1/2	1/4	3 1/4	4	4
H350-TB	3 1/2	4 3/4	4 3/4	4 3/4	4	4	1/4	3 3/4	4 1/2	4 1/2
H400-TB	4	5 1/8	5 1/8	5 1/8	4 1/2	4 1/2	1/4	4 1/4	5	5
H500-TB	5	6 1/4	6 1/4	6 1/4	5 1/2	5 1/2	1/4	4 3/4	6	6
H600-TB	6	7 1/8	7 1/8	7 1/8	6	6	3/8	5 1/4	7	7

Material – Hub and Locknut: Zinc or copper-free aluminum
 Insulating Throat: Thermoplastic temp. rating – 105° C
 Flammability Rating – 94V-0
 Sealing Ring: Nitrile (BUNA "N")

For Aluminum Hubs, add suffix A (i.e., H050A). For Chrome-Plated Hubs, add suffix CP (i.e., H050CP). For 316 Stainless Steel Hubs, add suffix GRSS (i.e., H050GRSS). (1/2" through 2" only.) Meets NEMA sealing requirements for NEMA 3R, 4 & 13 enclosures. CP and SST hubs are also rated NEMA 4X and 12.

UL Listed per NEC® 501.10(B). CSA Certified for hazardous locations Class II Groups E, F, G, Class III

UL File No. E-23018 CSA File No. 4484

Chrome-Plated Hubs (suffix-"CP"s) are rated NEMA 4X.

